

The Wells Cargo logo is a black circle with the words "WELLS" and "CARGO" stacked vertically in white, bold, sans-serif capital letters. The background of the entire advertisement is a photograph of a person in safety gear (orange jacket, orange helmet with a clear face shield, and yellow gloves) using a chainsaw to cut a large log. The log is being loaded onto a black Wells Cargo FastTrac trailer. The trailer has a side door with a silver handle and latch, and a "WELLS CARGO" logo on the front panel. The trailer is a single-axle unit with two wheels and a hitch at the front. The background is a blurred outdoor setting, likely a logging site.

**WELLS  
CARGO®**

# **FASTTRAC® 8.5' WIDE THE ALL PURPOSE TRAILER**

## **VALUE-DRIVEN WITH A SPIRIT THAT'S BORN TO HAUL!**

The FastTrac® brings a whole new level of value to the light-duty recreational cargo trailer market. A balanced combination of versatility and affordability, the FastTrac® delivers on all fronts. From its unpretentious styling to its uncompromising dependability, only Wells Cargo® could pack so much value into an entry-level trailer.

Trailer shown features Deluxe Package available at an additional charge.

**FASTTRAC®**

# SPECIFICATIONS



	FT85162	FT85202	FT85242
<b>Body:</b> Length Width	18' 0" 8' 4"	22' 0" 8' 4"	26' 0" 8' 4"
<b>Overall:</b> Length Width Height	20' 0" 8' 6" 8' 3"	24' 0" 8' 6" 8' 3"	28' 0" 8' 6" 8' 3"
<b>Interior:</b> Length Width Height	17' 9" 8' 1" 6' 6"	21' 9" 8' 1" 6' 6"	25' 9" 8' 1" 6' 6"
<b>Width Between Wheel Wells</b>	83"	83"	83"
<b>Platform Height</b>	20"	20"	20"
<b>Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity</b>	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
<b>Electric Brakes with Breakaway Kit</b>	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tire Size Tire Load Range</b>	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
<b>Hitch Ball Size</b>	2-5/16"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>	19"	19"	19"
<b>Hitch Weight (% of Curb Weight)</b>	10% to 15%	10% to 15%	10% to 15%
<b>Curb Weight (Approximate)</b>	2,485 lbs.	2,975 lbs.	3,465 lbs.
<b>GVWR</b>	7,000 lbs.	7,000 lbs.	7,000 lbs.
<b>Payload Capacity (Approximate)</b>	4,515 lbs.	4,025 lbs.	3,535 lbs.
<b>Rear Ramp Door Opening - Width x Height</b>	94" x 72"	94" x 72"	94" x 72"
<b>Side Door Opening - Width x Height</b>	32" x 72"	32" x 72"	32" x 72"
<b>12v Trailer End Connector</b>	7-way	7-way	7-way
<b>Tube Main Rails</b>	2" x 6"	2" x 6"	2" x 6"

## STANDARD FEATURES

- Exclusive Bull Nose Profile
- 15" Radial Tires with Silver Spoke Wheels
- Smooth Aluminum Radius Fenderettes
- White .024 Aluminum Exterior (With Screws)
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting (New LazerMax exclusive clearance light)
- 12v LED Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist & 16" Ramp Extension
- 32" Side Door with Bar Lock
- 12v Dome Light with Self-Switch
- Economy Sidewall Liner
- 3/4" High Performance PlexCore™ Decking
- 500 lb. Surface Wall Mounted Rope Rings (4)
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
- Undercoated Chassis
- 16" OC Vertical Posts
- 16" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty

## DELUXE PACKAGE UPGRADES

- .030 Aluminum Exterior
- ATP Nose Trim
- Exterior Color Options
- 3/8" PlexCore™ Sidewall Liner
- 5,000 lb. Floor D-Rings (4)



Trailers shown features Deluxe Package available at additional charge.



Standard Interior Shown with Economy Wall Liner & 500 lb. Rope Rings



www.wellscargo.com

Wells Cargo reserves the right to change or alter any specification, feature, option, package and/or pricing **without** notice. Some trailers are shown with optional equipment available at additional charge. See your authorized Wells Cargo dealer for more information.