

## Haulmark®

## ENHANCED VALUE

**THERE'S A WIDE-WORLD  
OUT THERE. EXPERIENCE  
IT ALL!**

In life, there are no shortcuts to success, and you never settle for second best. Fueled by relentless innovation, the Transport® V-Nose is a value-packed combination of performance, durability, and low-maintenance. Our trailers defy the routine and are designed to dominate every type of cargo hauling activity. At Haulmark®, we build trailers that work (and play) as hard as you do.



*Trailer shown features optional equipment available at an additional charge.*

## TRANSPORT®

# SPECIFICATIONS

**TRANSPORT**

	TSV58S2	TSV610S2	TSV612S2	TSV612T2	TSV712T2	TSV714T2	TSV716T2
<b>Body:</b> Length Width	9' 6" 5' 0"	11' 6" 6' 0"	13' 6" 6' 0"	13' 6" 6' 0"	13' 6" 7' 0"	15' 6" 7' 0"	17' 6" 7' 0"
<b>Overall:</b> Length Width Height	11' 4" 6' 8" 7' 1"	14' 0" 7' 8" 8' 1"	16' 0" 7' 8" 8' 1"	16' 0" 7' 8" 8' 2"	16' 0" 8' 6" 8' 2"	18' 0" 8' 6" 8' 2"	20' 0" 8' 6" 8' 2"
<b>Interior:</b> Length Width Height	9' 3" 4' 9" 5' 6"	11' 3" 5' 9" 6' 6"	13' 3" 5' 9" 6' 6"	13' 3" 5' 9" 6' 6"	13' 3" 6' 9" 6' 6"	15' 3" 6' 9" 6' 6"	17' 3" 6' 9" 6' 6"
<b>Platform Height</b>	17"	17"	17"	18"	18"	18"	18"
<b>Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity</b>	Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
<b>Electric Brakes with Breakaway Kit</b>	N/A	Optional	Optional	Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tire Size Tire Load Range</b>	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
<b>Hitch Ball Size</b>	2"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>	16"	16"	16"	17"	17"	17"	17"
<b>Hitch Weight (% of Curb Weight)</b>	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
<b>Curb Weight (Approximate)</b>	975 lbs.	1,195 lbs.	1,325 lbs.	1,740 lbs.	1,975 lbs.	2,125 lbs.	2,275 lbs.
<b>GVWR</b>	2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
<b>Payload Capacity (Approximate)</b>	2,015 lbs.	1,795 lbs.	1,665 lbs.	5,260 lbs.	5,025 lbs.	4,875 lbs.	4,725 lbs.
<b>Rear Door Opening - Width x Height</b>	54" x 60"	66" x 72"	66" x 72"	66" x 72"	78" x 72"	78" x 72"	78" x 72"
<b>Pass-Thru Door Opening - Width x Height</b>	N/A	36" x 72"	36" x 72"	36" x 72"	36" x 72"	36" x 72"	36" x 72"
<b>Cargo Control</b>	500 lb. Wall Rope Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings
<b>12v Male Connection</b>	4-way	4-way	4-way	7-way	7-way	7-way	7-way
<b>Tube Main Rails</b>	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"	2" x 4"	2" x 4"

## STANDARD FEATURES

- V-Front/Flat Roof Profile
- Spring Axles with E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit *(Tandem Axle Models Only)*
- Silver Mod Wheels with 15" Radial Tires
- Smooth Aluminum Radius Fenders
- 24" ATP Stoneguard
- .030 Aluminum Bonded Exterior *(No Screws)*
- 1-Piece Aluminum Roof
- 12v LED Slim Line Tail Lights
- 12v LED Clearance Lights
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist *(Single Swing Door on 5x8 Model)*
- 16" Ramp Extension
- 36" Side Entry Door with Flush Lock *(No Side Door on 5x8 Model)*
- 12v LED Dome Lights with Wall Switch
- 3/4" PlexCore™ Flooring
- 3/8" PlexCore™ Sidewall Liner
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- 3-Year Limited Warranty



Trailers shown feature optional equipment available at an additional charge.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark® dealer for more information.