

# ROAD FORCE® V-FRONT MUSCLE TO MOVE

### THE TRAILER THAT POWERS YOUR PASSION.

Designed and built by Wells Cargo<sup>®</sup>, the company that pioneered the cargo trailer industry over 65 years ago, the feature-rich Road Force<sup>®</sup> V-Front delivers a whole new level of value. From the rugged triple 16's (OC) tubular steel frame to the LED tail lights, the Road Force<sup>®</sup> V-Front is no stranger to quality. So for the price of an "ordinary" trailer, you can step up to the quality and value of the extraordinary Road Force<sup>®</sup> V- Front.

Trailer shown features optional equipment available at an additional charge.





#### **SPECIFICATIONS**

		RFV58S2	RFV610S2	RFV612S2	<b>RFV612T2</b>	RFV712T2	RFV714T2	RFV716T2
Body:	Length Width	9' 6" 5' 0"	11' 6" 6' 0"	13' 6" 6' 0"	13' 6" 6' 0"	13' 6" 7' 0"	15' 6" 7' 0"	17' 6" 7' 0"
Overall:	Length Width Height	11' 6" 6' 8" 7' 2"	14' 0" 7' 8" 8' 1"	16' 0" 7' 8" 8' 1"	16' 0" 7' 8" 8' 2"	16' 0" 8' 6" 8' 2"	18' 0" 8' 6" 8' 2"	20' 0" 8' 6" 8' 2"
Interior:	Length : Width Height	9' 1" 4' 9" 5' 6"	11' 3" 5' 9" 6' 6"	13' 3" 5' 9" 6' 6"	13' 3" 5' 9" 6' 6"	13' 3" 6' 9" 6' 6"	15' 3" 6' 9" 6' 6"	17' 3" 6' 9" 6' 6"
Platform Height		17"	17"	17"	18"	18"	18"	18"
Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity		Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Electric Brakes with Breakaway Kit		N/A	Optional	Optional	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Ti Tire Loa		ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ba	III Size	2"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch He	eight to Top of Ball	16"	16"	16"	17"	17"	17"	17"
Hitch We	eight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb We	eight (Approximate)	975 lbs.	1,195 lbs.	1,325 lbs.	1,740 lbs.	1,975 lbs.	2,125 lbs.	2,275 lbs.
GVWR		2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Payload	Capacity (Approximate)	2,015 lbs.	1,795 lbs.	1,665 lbs.	5,260 lbs.	5,025 lbs.	4,875 lbs.	4,725 lbs.
Rear Do	oor Opening - Width x Height	54" x 60"	66" x 72"	66" x 72"	66" x 72"	78" x 72"	78" x 72"	78" x 72"
Side Ent	ry Door Opening - Width x Height	N/A	36" x 72"	36" x 72"	36" x 72"	36" x 72"	36" x 72"	36" x 72"
12v Mal	e Connection	4-way	4-way	4-way	7-way	7-way	7-way	7-way
Tube Ma	in Rails	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"	2" x 4"	2" x 4"
		the second se		A REAL PROPERTY AND				

ROAD FORCE

## STANDARD FEATURES

- Exclusive Bull Nose Profile/Flat Roof
- 15" Radial Tires with Silver Spoke Wheels
- Fenders: 5' & 6' Wide = ATP Jeep 7' Wide = ATP Teardrop
- .030 Aluminum Bonded Exterior (Smooth Appearance)
- 1-Piece Aluminum Roof
- 12v LED Slim Line Clear Lens Tail Lights
- 12v LED Clear Lens Clearance Lights
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist (Single Swing Door on 5x8 Model)
- 16" Ramp Extension
- 36" Side Entry Door with Flush Lock (No Side Door on 5x8 Model)
- 12v LED Dome Light with Wall Switch
- 3/4" PlexCore™ High Performance Decking
- 3/8" PlexCore™ High Performance Sidewall Liner
- 5,000 D-Rings with Welded Backer Plate (4)
- Spring Axles with E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit (Tandem Axle Models Only)
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- 3-Year Limited Warranty

©Wells Cargo® 2024 Form WC\_RFV\_Flyer\_0124





Trailers shown feature <u>optional</u> equipment available at additional cost.



#### www.wellscargo.com

Specifications, features, options, packages & pricing subject to change <u>without</u> notice. See your authorized Wells Cargo® dealer for more information.