



Standard Features

COUPLER:	2 5/16" Adjustable Channel Mount Ball
SAFETY CHAINS:	5/16" Grade 70 w/Grab Hooks
AXLES:	2 - 7,000 Lb EZ Lube, Electric Brakes
SUSPENSION:	Rubber Torsion, Drop
TIRES:	ST235/80R16 Radial 10 Ply
MAIN FRAME:	6"- 7" C Channel
POCKETS:	Preformed 3/16" c/w Full Length 3/8" Rub Rail
CROSS-MEMBERS:	Channel - 3" on 18" Centers
FENDERS:	14 ga Tread Plate
LIGHTS:	LED, Rubber Mounted
DECKING:	Douglas Fir, Heat Treated
JACK:	1 - 12,000 Lb Jack
TOOLBOX:	A Frame (Hydraulic Housing)
HYDRAULICS:	Single Cylinder, Power Up & Power Down
FINISH:	6 Step Powder Coating Process. 1. Blast, 2. Phosphate Wash & Sealer Rinse, 3. Dry, 4. Zinc Primer, 5. Sherwin Williams Dry on Dry Color, 6. Cure Oven

PRO Series

MODEL: HT147

15,400-17,500 Lb GVWR

Available Sizes:

- 7' x 18'
- 7' x 20'
- 7' x 22'
- 7' x 24'

Popular Options

- Fender Guards (Pipe)
- Weld On 4" D Ring
- Aluminum Wheel Upgrade

SEE DEALER FOR COMPLETE LIST OF AVAILABLE OPTIONS




WHEEL OPTIONS

SUBJECT TO AVAILABILITY



BLACK
STANDARD



WHITE
STANDARD



ALUMINUM
UPGRADE

STANDARD COLOUR



BLACK

AVAILABLE COLOURS



RANGER GREEN



EQUIPMENT YELLOW



METALLIC CHARCOAL



ROYAL BLUE



SAND DUNE TAN



HAZARD ORANGE



ENVIRO GREEN



INDUSTRIAL GREEN



DOUBLE A RED



WHITE



ANSI GREY

