

DTX 16K 83" TELESCOPING DUMP

The telescoping cylinder of the DTX 16k dump trailer has massive dumping leverage, and the 3' sides are standard on this unit, which means you will have tons of hauling capability.



PULL TYPE

Bumperpull /
Gooseneck



LENGTH

12' - 16'



GVWR

14,000 -
17,500 lb



WIDTH

83"



SIDES

3' HIGH

MORE OPTIONS

COUPLERS

21K ADJUSTABLE PINTLE EYE
21K ADJUSTABLE PLATE
MOUNT PINTLE EYE
2 5/16" 30K ROUND GN
COUPLER
30K ROUND GN COUPLER KING
PIN

JACKS

2 - 10K DROP-LEG JACKS ON GN
1 - HYDRAULIC JACK
2 - HYDRAULIC JACKS ON GN

TONGUE/NECKS

STND HEIGHT I-BEAM NECK
(ADD. RISER BOX OR DECK-
OVER)
6" EXTENDED HEIGHT RISERS
NECK (ADD. RISER BOX OR
DECK-OVER)

SIDES

4' SOLID SIDES ON DUMP
TRAILER
3' FLARE/ SIDES ON DUMP
TRAILER

SUSPENSIONS

4" DROP WITH SLIPPER SPRING
SUSPENSION

WHEEL/TIRES

ST235/85R16 G RADIAL TIRES
ON 2-7K
ST215/75R17.5 H RADIAL TIRES
ON SINGLES

FLOORS

3/16" FLOOR ONLY/10 GAUGE
SIDES

TARPS

FLIP-OVER TARP SYSTEM

SPARES

SPARE ST235/80R16 E RADIAL
TIRE
SPARE ST235/85R16 G RADIAL
TIRE
SPARE ST215/75R17.5 H RADIAL
TIRE ON SINGLE

D-RINGS

EXTRA 1/2" BULL-NOSE D-
RINGS

OTHER OPTIONS

RECEIVER HITCH
7-WATT SOLAR PANEL
FORK POCKETS
UNDER FRAME OVERSIZED
TOOL TRAY

STANDARD FEATURES

2 5/16" ADJUSTABLE COUPLER

1 - 10K DROP-LEG JACK

8" X 15LB I-BEAM TONGUE & FRAME WITH
TELESCOPING CYLINDER AND TOOLBOX

3" CHANNEL ON 12" CENTERS

3' SOLID SIDES ON DUMP TRAILER

NO DOVETAIL/7' SLIDE-IN RAMPS

2-8K ELECTRIC BRAKE AXLES

SLIPPER SPRING SUSPENSION

ST235/80R16 E RADIAL TIRES

DOUBLE BROKE DIAMOND PLATE FENDERS

10 GAUGE FLOOR AND SIDES

FLUSHMOUNT LED'S/STANDARD WIRING

PULL BACK TARP SYSTEM

WIRELESS REMOTE



MAXX-D

WET BLACK(STND) INDIGO BLUE METALLIC RUBY RED METALLIC

ARMY GREEN

MAXX-D GRAY METALLIC

DESERT TAN

SIGNAL BLUE

FLAME RED

KAWASAKI GREEN